



## Archem Grade 15WR Hi Flow Extra Low Dust Coated

Archem XLD15WR Extra Low Dust Coated anti set off powder, specifically designed for today's high speed modern Perfecting Presses to prevent Ink set off in the stack when printing on 30gsm to 200gsm substrates. The quoted stock gsm range for this specific grade is intended as a guide only. The correct micron size to use will also depend on other factors such as type of paper, weight of ink film etc. Non-absorbent substrates may require a larger micron spray powder.

### Technical specification

❖ Appearance	Dry white powder.
❖ Materials content	Vegetable starch.
❖ Average granule diameter	15 $\mu$ (microns).
❖ Moisture	11% - 13% (Certificate of Analysis available)
❖ Hydrophobic characteristics	Positive (hydrophobic)
❖ Spray and Flow rate	Excellent

### Product Benefits

- ❖ Increased economy of use due to extra low dust 2% of particles are less than 10 $\mu$
- ❖ Extremely narrow particle range, 0% particles less than 5 $\mu$  giving full value for money
- ❖ Reduced Plate wear and piling on the Printing Blankets through no over spraying.
- ❖ Designed for use on Straight through or Long Perfect Presses.
- ❖ Ultra uniform spray pattern giving flat stacks for follow on trades improving productivity.
- ❖ Highly controllable flow rate giving reduced machine settings.
- ❖ Biodegradable.

### Directions for use

Suitable for all Sheetfed lithographic printing - single pass, multiple pass work and in conjunction with Water based Coatings. Always apply the minimum amount of spray powder required to prevent set off. Archem PRS anti-set off spray powders are developed for use in all types of spray powder applicators. Should be stored at room temperature in dry conditions, containers should be resealed after use to prevent the powder becoming damp or contaminated.

### Packaging

1kg    2.5kg    3kg    20kg

