



Archem PRS Ltd
Unit E303
Eastgate
Warmco Industrial Park
Mossley
OL5 9AY

Email: production@archem.co.uk

Archem PRS Grade 2500S Uncoated

Archem PRS 2500S is an uncoated, starch based anti set off powder, designed to prevent Ink set off in the stack when printing on 250gsm to 400gsm substrates. The quoted stock gsm range for this specific grade is intended as a guide only. The correct micron size to use will be determined by other factors such as type of paper, weight of ink film etc. Non-absorbent substrates may require a larger micron spray powder. Ideal for Multi pass work or where follow on trades such as lamination, foil blocking or UV varnishing are being used.

Technical specification

❖ Appearance	Dry white powder.
❖ Materials content	Vegetable starch.
❖ Average granule diameter	25 μ (microns).
❖ Moisture	11% - 14% (Certificate of Analysis available)
❖ Hydrophobic characteristics	Negative (non-hydrophobic)
❖ Spray and Flow rate	Good

Product Benefits

- ❖ Uncoated (non-hydrophobic) spray powder excellent for multi pass work & following trades.
- ❖ Narrow particle range.
- ❖ Uniform spray pattern.
- ❖ Reduced Plate wear and piling on the Printing Blankets.
- ❖ Cost effective and economical.
- ❖ Highly controllable flow rate.
- ❖ Biodegradable.

Directions for use

Suitable for all Sheetfed lithographic printing - single pass, multiple pass work and in conjunction with Water based Coatings. Always apply the minimum amount of spray powder required to prevent set off. Archem PRS anti-set off spray powders are developed for use in all types of spray powder applicators. Should be stored at room temperature in dry conditions, containers should be resealed after use to prevent the powder becoming damp or contaminated.

Packaging

1kg 2.5kg 3kg 20kg

